

<u>BLADE 550 LTX EPS</u>





Technical Specification

Engine Type	503 cc,Single Cylinder, SOHC
Ignition	ECU
Starter	Electric
Bore X Stroke	Ø 92 × 75.6 mm
Compression Ratio	10.2
Fuel System	38 mm Throttle Body / Programmed Fuel Injection
Max Power	38.7 HP / 6500 rpm
Max Torque	46.1 Nm / 5500 rpm
Drive System	4 × 4 Shaft Drive
Gear Selection	L/H/N/R/P
Transmission	V-Belt CVT Automatic
Engine Braking System	Standard
Over Ride Button	Standard
Front Suspension	Dual A-arm
Rear Suspension	Dual A-arm with Anti-roll Bar
Front / Rear Brake	Hydraulic Disc with piston caliper and Hydraulic Foot
	Brake
Parking Brake	Park In Transmission / Lockable Hand Lever
Front Tire	AT 25 × 8 – 12 , 6 PLY
Rear Tire	AT 25 × 10 – 12 , 6 PLY
Wheelbase (mm)	1450
Overall Length (mm)	2360
Overall Width (mm)	1235
Overall Height (mm)	1280
Fuel Capacity	18 L
Electrical Outlet Connector	2 DC 12V 10A 120W
Instrumentation	Digital instrument panel with odometer,
	TFT speedmeter, Tripmeter, RPM, transmission
	position, fuel gauge, Hi-Temp/Low-Battery lights,
	high beam light, EFI checking, differential indicator,
	2WD/4WD indicator, EPS indicator
Color	Matte Grey

BLADE 550 LTX EPS



New TFT color display

-0 ලපා පො :::D km/h 12.1 v 🕹 0.1 hr ODO E TT 57 °c EPS MAX 0 km









