

## BLADE 520 EPS 4X4 Rigid





## **Technical Specification**

## BLADE 520 EPS 4X4 Rigid

Engine Type	503 cc,Single Cylinder, SOHC
Ignition	ECU
Starter	Electric
Bore X Stroke	Ø 92 × 75.6 mm
Compression Ratio	10.2
Fuel System	38 mm Throttle Body / Programmed Fuel Injection
Max Power	38.7 HP / 6500 rpm
Max Torque	46.1 Nm / 5500 rpm
Drive System	4 × 4 Shaft Drive
Gear Selection	L/H/N/R
Transmission	V-Belt CVT Automatic
Engine Braking System	Standard
Over Ride Button	Standard
Front Suspension	Dual A-arm
Rear Suspension	RIGID with Dual Shock Absorbers
Front / Rear Brake	Hydraulic Disc with piston caliper and Hydraulic Foot
	Brake
Parking Brake	Lockable Hand Lever
Front Tire	AT 25 × 8 – 12 , 6 PLY
Rear Tire	AT 25 × 10 – 12 , 6 PLY
Wheelbase (mm)	1290
Overall Length (mm)	2155
Overall Width (mm)	1240
Overall Height (mm)	1280
Fuel Capacity	18 L
Electrical Outlet Connector	2 DC 12V 10A 120W
Instrumentation	Digital instrument panel with odometer, speedmeter,
	Tripmeter, RPM, transmission position, fuel gauge,
	Hi-Temp/Low-Battery lights, high beam light, EFI
	checking, differential indicator, 2WD/4WD indicator,
	EPS indicator
Color	Grey







